

TIRE CHANGER · HEAVY-DUTY

C201GBL

Compact Swing Arm Tire Changer

Swing arm design

Rim Width **315 mm**

Max. Wheel Diameter **960 mm**

Powers **0.75 kW / 1.1 kW**

Operation Speed **6 rpm**



What sets the C201GBL apart

01 Flat tire demounting head

Special material demounting head with thicker hexagonal shaft is suitable for flat tire demounting.

02 Large Ø185 cylinder

2000–2500 kgf pressure output for heavy-duty demounting needs.



03 Manganese steel disk

Hardness, wear resistance and impact resistance for long time operation.



C201GBL specifications

Outside Clamping Range	10-21''	Powers	0.75 kW / 1.1 kW
Inside Clamping Range	12-24''	N./G. Weight	175 / 200 kg
Rim Width	315 mm	Packing DIM	970 × 770 × 850 mm
Max. Wheel Diameter	960 mm	Machine-Space DIM	1800 × 1800 × 2200 mm
Work Pressure	8-10 bar	Noise	<70 dB
Operation Speed	6 rpm	Max QTY In Container	36 pcs (20'') & 72 pcs (40'')
Voltages	110V / 220V / 380V		

 20-inch tire lever	 Hex-rod cap	 Hex-rod spring	 Press-rod cap	 Multi-function inflator gun	 Mounting-head gasket
 Bracket	 Brush	 Oil cup	 Adjusting nut		

1998 FOUNDED · HK-OWNED	60+ EXPORT COUNTRIES	CE-ISO 9001:2015 CERTIFIED	OEM ODM AVAILABLE
-----------------------------------	--------------------------------	--------------------------------------	-----------------------------

Request a quotation for the C201GBL
carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

