

TIRE CHANGER · SWING ARM

C211GB+NAAL

Swing Arm Tire Changer with Assist Arm

2500kgf aluminum alloy tire press cylinder

Applicable outer clamping 10"-21"

Applicable inside clamping 12"-24"

Max. wheel width 315mm

Max. wheel diameter 960mm

C211GB+NAAL

PRODUCT IMAGE COMING SOON



What sets the C211GB+NAAL apart

1

Swing arm design.

2

2500kgf aluminum alloy tire press cylinder.

3

New hexagonal press rod sheath adjusts for misalignment.

4

Ergonomic design, more convenient to dismount flat, wide

5

High Precision Large Turntable serve up to 24 inch rim.

6

body and super hard anti-explosion tires.

C211GB+NAAL specifications

Applicable outer clamping	10" - 21"	Tire-pressed shovel force	2000-2500kgf
Applicable inside clamping	12" - 24"	Optional volt	110V/220V
Max. wheel width	315mm	N./G. Weight	205/230kg, 75/88kg(NAAL)
Max. wheel diameter	960mm	Packing DIM	9707701000mm, 1150520300mm(NAAL)
Working air pressure	8-10bar		

					
20-inch tire lever	Hex-rod cap	Clamp-jaw covers	Press-rod cap	Bead-breaker blade cover	Inflation gauge
					
Tire-lever cover	Bracket	Brush	Oil cup	Adjusting nut	Mounting-head gasket

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the C211GB+NAAL

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

