

TIRE CHANGER • SWING ARM

C211GCIT+NAA

Swing Arm Tire Changer with Assist Arm

2000-2500kgf aluminum alloy tire press cylinder

Applicable outer clamping 10"-24"

Applicable inside clamping 12"-26"

Max. wheel width 315mm

Max. wheel diameter 960mm



What sets the C211GCIT+NAAL apart

-
- 01 **Swing arm design.**
 - 02 **2000-2500kgf aluminum alloy tire press cylinder.**
 - 03 **New hexagonal press rod sheath adjusts for misalignment.**
 - 04 **High Precision Large Turntable serve up to 24 inch rim.**



C211GCIT+NAAL specifications

Applicable outer clamping	10"-24"	Optional volt	110V/220V
Applicable inside clamping	12"-26"	N./G. Weight	205/230kg, 75/88kg(NAAL)
Max. wheel width	315mm	Packing DIM	11507701000mm, 1150520300mm(NAAL)
Max. wheel diameter	960mm	20" container	24pcs
Working air pressure	8-10bar	40" container	54pcs
Tire-pressed shovel force	2000-2500kgf		

					
20-inch tire lever	Hex-rod cap	Clamp-jaw covers	Press-rod cap	Bead-breaker blade cover	Inflation gauge
					
Tire-lever cover	Bracket	Brush	Oil cup	Adjusting nut	Mounting-head gasket

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the C211GCIT+NAAL

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

