

TIRE CHANGER • SWING ARM

C211GC

Swing Arm Tire Changer

2000-2500kgf aluminum alloy tire press cylinder

Applicable outer clamping 11"-24"

Applicable inside clamping 13"-26"

Max. wheel width 350mm

Max. wheel diameter 1080mm



What sets the C211GCIT apart

-
- 01 **Swing arm design.**
 - 02 **2000-2500kgf aluminum alloy tire press cylinder.**
 - 03 **New hexagonal press rod sheath adjusts for misalignment.**
 - 04 **High Precision Large Turntable serve up to 24 inch rim.**



C211GCIT specifications

Applicable outer clamping	11"-24"	Optional volt	110V/220V
Applicable inside clamping	13"-26"	N./G. Weight	260/285kg
Max. wheel width	350mm	Packing DIM	11507701000mm
Max. wheel diameter	1080mm	20" container	30pcs
Working air pressure	8-10bar	40" container	60pcs
Tire-pressed shovel force	2000-2500kgf		

					
20-inch tire lever	Hex-rod cap	Clamp-jaw covers	Press-rod cap	Bead-breaker blade cover	Inflation gauge
					
Tire-lever cover	Bracket	Brush	Oil cup	Adjusting nut	Mounting-head gasket

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the C211GCIT

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

