

TIRE CHANGER • LEVERLESS

C299MA

Professional Center-Post Leverless Tire Changer

Side-swinging structure of sliding arm assembly

Rim Range 13-28"

Rim Width 350 mm

Max. Wheel Diameter 1180 mm

Powers 1.1 kW



What sets the C299MAX apart



Side-swing sliding arm assembly

Automatic flip changer head adapts to different tire sizes/types with precise angle.

— COSENG · C299MAX

— MORE FEATURES

2

Synchronized dual-disc structure

Separated pressure plate and tray enable efficient tire/wheel shift.

3

Precision servo motor


High-precision position control; adjustable speed from zero to max.

Components & build detail

Key components and assemblies of the C299MAX.



Upper & lower bead-breaker arms



Center-post worktable



Tire support rack



Cabinet



Auxiliary arm

C299MAX specifications

Rim Range	13-28''	Tire Lift Max Loading	75 kg
Rim Width	350 mm	N./G. Weight	456 / 510 kg
Max. Wheel Diameter	1180 mm	Packing DIM	1100 × 1500 × 2040 mm
Work Pressure	8-10 bar	Machine-Space DIM	1800 × 1800 × 2200 mm
Operation Speed	0-12 rpm	Noise	<70 dB
Voltages	110V / 220V	Max QTY In Container	10 pcs (20'') & 20 pcs (40'')
Powers	1.1 kW		

 Oversized cone	 Bead presser plate	 Reverse-mount adapter	 Plastic & metal tire levers	 Riser plate	 Bracket
 Brush	 Lubricant paste	 Measuring gauge	 Inspection mirror	 Mounting-head gasket	

1998 FOUNDED · HK-OWNED	60+ EXPORT COUNTRIES	CE-ISO 9001:2015 CERTIFIED	OEM ODM AVAILABLE
-----------------------------------	--------------------------------	--------------------------------------	-----------------------------

Request a quotation for the C299MAX
carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

