

TIRE CHANGER • LEVERLESS

C299SUPER

Professional Center-Post Leverless Tire Changer

Vertical-lifting column structure — spacious operating
area

Rim Range 14-34"

Rim Width 400 mm

Max. Wheel Diameter 1180 mm

Powers 0.75 / 1.1 kW



What sets the C299SUPER apart



One-key return

Return to a preset position with a single key press.

— COSENG · C299SUPER

— MORE FEATURES

1

Durable construction

Solid one-piece structure enhances strength and longevity.

2

Synchronized dual-disc structure

Separated pressure plate and tray enable efficient tire/wheel shift.

4

Precision servo motor


High-precision position control; adjustable speed from zero to max.

Components & build detail

Key components and assemblies of the C299SUPER.



Upper & lower bead-breaker arms



Center-post worktable



Tire support rack



Cabinet



Auxiliary arm

C299SUPER specifications

Rim Range	14-34''	Operation Speed	0-12 rpm
Max. Wheel Diameter	1180 mm	Powers	0.75 / 1.1 kW
Rim Width	400 mm	N./G. Weight	479 / 527 kg
Work Pressure	8-10 bar	Machine-Space DIM	1800 × 1800 × 2200 mm
Voltages	110V / 220V	Packing DIM	1320 × 770 × 2040 mm
Tire Lift Max Loading	75 kg	Max QTY In Container	8 pcs (20'') & 18 pcs (40'')
Noise	<70 dB		

					
Oversized cone	Bead presser plate	Reverse-mount adapter	Plastic & metal tire levers	Riser plate	Bracket
					
Brush	Lubricant paste	Measuring gauge	Inspection mirror	Mounting-head gasket	

1998 FOUNDED · HK-OWNED	60+ EXPORT COUNTRIES	CE-ISO 9001:2015 CERTIFIED	OEM ODM AVAILABLE
---	--	--	---

Request a quotation for the C299SUPER

carson@coseng.com.cn

+86 137 2785 7065

No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

