

MOBILE FITTING

CZ288

Mobile Fitting Tire Changer

Pneumatic locking swing arm design

Powers 0.85 kW

Voltages 24V / 110V / 220V

Outside clamping range 10-21''

Inside clamping range 12-24''



What sets the CZ288 apart

1

Pneumatic locking swing arm

Pneumatic locking swing arm design.

2

Auxiliary arm rotation

Three-joint auxiliary arm can rotate 350° around the center.

3

Pry-free automatic bird head

Suitable for handling tires of various sizes across vehicle types.

4

DAS assist arm

Smoother running, stronger structure; improves efficiency.

5

High-performance integrated motor

Real-time load adjustment to improve energy efficiency and reduce consumption.

6

Large Ø185 cylinder

2000–2500 kgf pressure output for demounting needs.

7

Manganese steel disk

Hardness/wear/impact resistance for long time operation.

CZ288 specifications

Outside clamping range	10-21''	Powers	0.85 kW
Inside clamping range	12-24''	N./G. weight	215 / 247 kg
Rim width	300 mm	Packing DIM	1000 × 850 × 1350 mm
Max. wheel diameter	960 mm	Machine-space DIM	1200 × 1200 × 1200 mm
Work pressure	8-10 bar	Noise	<70 dB
Operation speed	6 rpm	Max QTY In Container	13 pcs (20'') & 26 pcs (40'')
Voltages	24V / 110V / 220V		

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the CZ288

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

