

WHEEL BALANCER • MOBILE

CZ301

Mobile Wheel Balancer

Flip-up base — small enough to carry and transport

Rim Range **10-30"**

Rim Width **415 mm**

Max. Wheel Diameter **1080 mm**

Balancer Accuracy **±1 g**



What sets the CZ301 apart

01 Flip-up base plate

Saves space; small enough to be carried and transported.

02 High-precision detection points

High-precision detection points.



CZ301 specifications

Rim Range	10-30''	Voltages / Power	110V / 220V · 0.25 kW
Shaft size	36 mm	N./G. Weight	58 / 66 kg
Rim Width	415 mm	Packing DIM	800 × 600 × 920 mm
Max. Wheel Diameter	1080 mm	Machine DIM	1300 × 517 × 578 mm
Balancer Accuracy	±1 g	Noise	<70 dB
Balancer Speed	150-220 rpm	Max QTY In Container	42 pcs (20'') & 84 pcs (40'')
ALU-Mode	6		

					
Cone 100-132 mm	Cone 44-65 mm	Cone 54-79 mm	5 mm & 8 mm hex wrenches	Cone 74-109 mm	Spindle lead screw
					
Extended caliper head	Caliper	Plastic cup	Tool hanger	Weight pliers	Wheel weights
					
Quick-release nut	Threaded shaft & Lead screw	Threaded shaft			

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the CZ301

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

