

WHEEL BALANCER · MAGNETIC LEVITATION

SP711N

Magnetic Levitation Balancer with Cross Laser

Magnetic Levitation Drive

Wheel hub diameter range **10"-30"**

Max. wheel width **415mm**

Max. wheel diameter **1080mm**

Distance to spin flange **10"**



What sets the SP711N apart

1

Magnetic levitation system (MLS) and self propelled balancing (SPBU).

2

512 angular positions.

3

Smart position locator (SPL).

4

Liner optical encoder (LOE).

5

Advanced spin brake (ASB).

6

Automatic distance and diameter measurement.

SP711N specifications

Wheel hub diameter range	10"-30"	Operation display interface	Large press keyboard
Max. wheel width	415mm	Detective location	512
Max. wheel diameter	1080mm	Ounce/Gram conversion option	yes
Distance to spin flange	10"	ALU mode	8
Maximum tire weight	80kg	Net / Gross Weight	120/140kg
Balance accuracy	1g	Optional volt	110V/220V
Balance speed	150-180RPM	Packing DIM	9777115cm

					
Cone 100-132 mm	Cone 44-65 mm	Cone 54-79 mm	5 mm & 8 mm hex wrenches	Cone 74-109 mm	Spindle lead screw
					
Extended caliper head	Caliper	Plastic cup	Tool hanger	Weight pliers	Wheel weights
					
Quick-release nut	Threaded shaft & Lead screw	Threaded shaft			

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the SP711N

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

