

TIRE CHANGER • HEAVY-DUTY

TC201GB+DAS

Swing Arm Tire Changer with DAS Assist Arm

Heavy-duty changer with dual assist arms

Rim Width **315 mm**

Max. Wheel Diameter **960 mm**

Powers **0.75 kW / 1.1 kW**

Operation Speed **6 rpm**



What sets the TC201GB+DAS apart

1

Flat tire demounting head

Special material demounting head with thicker hexagonal shaft is suitable for flat tire demounting.

2

High-performance integrated motor

Real-time load-based adjustment to improve energy efficiency and reduce energy consumption.

3

Ergonomic design

More convenient to demount flat, wide-body and super-hard blast tires.

4

Swing arm design

Swing arm design.

5

DAS assist arm

Smoother running, stronger structure; improves working efficiency.

6

Large Ø185 cylinder

2000–2500 kgf pressure output for heavy-duty demounting needs.

7

Manganese steel disk

Hardness, wear resistance and impact resistance for long time operation.

TC201GB+DAS specifications

Outside Clamping Range	10-21''	Work Pressure	8-10 bar
Inside Clamping Range	12-24''	Voltages	110V / 220V / 380V
Rim Width	315 mm	N./G. Weight	195 / 220 kg
Max. Wheel Diameter	960 mm	Packing DIM	970 × 770 × 1000 mm
Operation Speed	6 rpm	Machine-Space DIM	1800 × 1800 × 2200 mm
Powers	0.75 kW / 1.1 kW	Max QTY In Container	36 pcs (20'') & 72 pcs (40'')
Noise	<70 dB		

03

STANDARD ACCESSORIES

Manganese Steel Crowbar

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the TC201GB+DAS

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

