

TIRE CHANGER · HEAVY-DUTY

TC201GB

Swing Arm Table-Top Tire Changer

Swing arm design

Rim Width **315 mm**

Max. Wheel Diameter **960 mm**

Powers **0.75 kW / 1.1 kW**

Operation Speed **6 rpm**



What sets the TC201GB apart

01 Flat tire demounting head

Special material demounting head with thicker hexagonal shaft is suitable for flat tire demounting.

02 Large Ø185 cylinder

2000–2500 kgf pressure output for heavy-duty demounting needs.

03 Manganese steel disk

Hardness, wear resistance and impact resistance for long time operation.



TC201GB specifications

Outside Clamping Range	10-21''	Powers	0.75 kW / 1.1 kW
Inside Clamping Range	12-24''	N./G. Weight	180 / 200 kg
Rim Width	315 mm	Packing DIM	970 × 770 × 1000 mm
Max. Wheel Diameter	960 mm	Machine-Space DIM	1800 × 1800 × 2200 mm
Work Pressure	8-10 bar	Noise	<70 dB
Operation Speed	6 rpm	Max QTY In Container	36 pcs (20'') & 72 pcs (40'')
Voltages	110V / 220V / 380V		

Manganese Steel Crowbar

1998

FOUNDED · HK-OWNED

60+

EXPORT COUNTRIES

CE-ISO

9001:2015 CERTIFIED

OEM

ODM AVAILABLE

Request a quotation for the TC201GB

carson@coseng.com.cn · +86 137 2785 7065 · No. 6 Shuanglin East Road, Jinwan District, Zhuhai, China

